

31.03.2025

Article	TEBO article	Size	Weight kg	Components %			
				PU foam VB1830	Carrier material - Polyester rail	Adhesive: acrylic emulsion	Silicone-coated polypropylene
B1029	5615	15x15x2000mm/2pcs	0.0162	36.00%	3.50%	33.50%	27.00%
B1005	331030	30x30x2000mm/1pcs	0.0320	69.00%	1.70%	16.30%	13.00%
B1009	5630	30x30x2000mm/2pcs	0.0640	69.00%	1.70%	16.30%	13.00%
B1020	33105	50x50x2000mm/1 pcs	0.0900	86.50%	0.80%	7.20%	5.50%
B1028	5650	50x50x2000mm/2 pcs	0.1800	86.50%	0.80%	7.20%	5.50%

Aliphatic and/or cycloaliphatic amine catalysts: use amine catalyst mixtures in low quantities - info from MSDS about amines is 1. Preparation of triethylenediamine and 2. Ethanamine 2,2-oxybis (N, N-dimethyl)

Flame - retardants - no use;

Plasticizers - no use;

Silicone and /or organic surfactants: use Polyether modified polytrioxane (composition is trade secret);

Inorganic Tin catalyst: VBI use Tin (I)- isoocatoate

Organic/or inorganic pigments: VBI use Reactint Gray X3LV, which is declared as colour reagent with no hazardous ingredients.